

Server: localhost

Datenbanken
 SQL
 Status
 Variablen
 Zeichensätze
 Formate
 Prozesse
 Exportieren
 Importieren

Servervariablen und -einstellungen

Variable	Wert für diese Sitzung / Globaler Wert
auto increment increment	1
auto increment offset	1
automatic sp privileges	ON
back log	50
basedir	/usr/local/
bdb cache size	8.388.600
bdb home	/var/db/mysql/
bdb log buffer size	262.144
bdb logdir	
bdb max lock	10.000
bdb shared data	OFF
bdb tmpdir	/tmp/
binlog cache size	32.768
bulk insert buffer size	8.388.608
character set client	utf8
(Globaler Wert)	latin1
character set connection	utf8
(Globaler Wert)	latin1
character set database	utf8
(Globaler Wert)	latin1
character set filesystem	binary
character set results	utf8
(Globaler Wert)	latin1
character set server	latin1
character set system	utf8
character sets dir	/usr/local/share/mysql/charsets/
collation connection	utf8_unicode_ci
(Globaler Wert)	latin1_swedish_ci
collation database	utf8_general_ci
(Globaler Wert)	latin1_swedish_ci
collation server	latin1_swedish_ci
completion type	0
concurrent insert	1
connect timeout	5
datadir	/var/db/mysql/
date format	%Y-%m-%d
datetime format	%Y-%m-%d %H:%i:%s
default week format	0
delay key write	ON
delayed insert limit	100
delayed insert timeout	300
delayed queue size	1.000
div precision increment	4
engine condition pushdown	OFF
expire logs days	0
flush	OFF
flush time	0
ft boolean syntax	+ -><()~*:""&
ft max word len	84
ft min word len	4
ft query expansion limit	20
ft stopword file	(built-in)
group concat max len	1.024
have archive	NO
have bdb	YES
have blackhole engine	NO
have compress	YES
have crypt	YES
have csv	NO
have dynamic loading	YES
have example engine	NO
have federated engine	YES